

Flash'n'Fill™ AFF/100



Properties

Enclosure: ABS Construction with IP Rating: 55

Supply Voltage/Frequency: 230V 50Hz

Fuse: 1AT 20mm x 5mm

Dimensions: 13 x 15 x 6 cm

Net weight: 0.5 Kg

Fixing: Wall-mounted at a maximum of 2m above the operator's floor.

Background

Flash'n'Fill™ is an independent electronic warning device which operates in conjunction with Float Switch Assemblies to detect low levels of chemical in up to ten chemical containers simultaneously. In an alarm situation a red beacon will flash to highlight that one of the containers is getting low on product and will require replenishment. At the same time an LED will be illuminated to draw attention to which chemical container needs replenishing and an audible warning will also sound intermittently; this can be stopped by pressing the mute button on the front of the unit. The sounder will activate again if another drum becomes empty. The sound can be stopped once again by pressing the mute button.



Product Technical Data Sheet

Features

- Selection of Float Switch Assemblies to suit a range of chemical containers.
- Suitable for use with viscous liquids.
- Easy to install and operate.
- Mute facility to disable the sounder mid-alarm.
- 24V or 110V input voltage options available.

Optional:

- Float switch Assemblies to suit 5-10L, 20-25L, 50-60L and 200L or IBC container.
 - AFF/200-35-10 – Float Switch Assembly for 5-10 Litre Container.
 - AFF/200-50-10 – Float Switch Assembly for 20-25 Litre Container.
 - AFF/200-75-10 – Float Switch Assembly for 50-60 Litre Container.
 - AFF/200-110-10 – Float Switch Assembly for 200 Litre Container or IBC.
- Float switch Assemblies for Viscous Liquids to suit 5-10L, 20-25L, 50-60L and 200L or IBC container.
 - AFF/400-35-10 – Float Switch Assembly for Viscous Liquid for 5-10 Litre Container.
 - AFF/400-50-10 – Float Switch Assembly for Viscous Liquid for 20-25 Litre Container.
 - AFF/400-75-10 – Float Switch Assembly for Viscous Liquid for 56-60 Litre Container.
 - AFF/400-110-10 – Float Switch Assembly for Viscous Liquid for 200 Litre Container or IBC.
- Can be programmed for normally open or normally closed Float Switch Assemblies.
- Relay for remote high volume sounder.

Approvals:

CE Compliant

For further information, see: [Declaration of Conformity](#)

Manufactured in the UK in an ISO9001-approved environment.

HS Commodity Code: 84349000