

High Volume Peristaltic Pump - 24V DC AHP/100-24



Properties

Motor/Gearbox: Anodised Aluminium/Copper

Pump Mounting Plate: Stainless Steel

Pump Housing: Glass filled Nylon

Inlet/Outlet Spigots: PVC, to suit 1/2" & 5/8" bore tube

Other Parts: PVC Rollers; Stainless Steel Spinner Assembly.

Supply Voltage: 24V DC

Running Current: 0.6 - 1.4 A

Capacity: Flow rate tested using water. Examples:

RPM	Tube material	Tube bore (mm)	Delivery Output (L/hour)
40	Santoprene	9.6	42
40	Santoprene	12.7	66
80	Santoprene	9.6	90
80	Santoprene	12.7	150
120	Santoprene	9.6	106
120	Santoprene	12.7	164
160	Santoprene	9.6	120
160	Santoprene	12.7	198

Please refer to tube chart for chemical compatibility.



Product Technical Data Sheet

Properties

Dimensions: 18.5 x 15.5 x 16.5 cm

Net weight: 1.5 Kg

Fixing: Wall-mounted at a maximum height of 3 m from the drum.

Background

The High Volume Peristaltic Pump (AHP/100-24) has been designed to operate on a standalone principle, although it can be fitted to operate as part of an existing system. It forms part of a range of rugged, reliable and easy to install high volume peristaltic pumps that have been produced as a reliable and accurate means of dosing a wide range of liquids. The unit has excellent suction performance enabling priming from dry, and pumped product only makes contact with the tube. The High Volume Peristaltic Pump is quiet, corrosion-resistant, easy to clean and inexpensive to maintain: spring loaded rollers extend the life of the tubes, reducing the need for replacements.

Features

- Pump tubes are not exposed and pumped product only makes contact with the tube.
- Spring loaded spinner assembly to increase the tube life.
- Positive displacement.
- Self-priming to a height of 3 metres.
- Easy to install and operate, with no back flow or siphoning.
- Quiet when running and very robust.

Optional:

- An IP55-rated plastic enclosure.
- An on/off switch allowing the pump to be turned off during maintenance such as tube changes.
- Available without a pump mounting plate.
- Silicone tubing instead of Santoprene.
- Inlet/Outlet Spigots to suit tubes with other bores.

Manufactured in the UK

HS Commodity Code: 84135040

Ambic Equipment Ltd does not provide a warranty on the usage of pumps. Therefore, it is recommended that customers carry out life tests for their application prior to use. The information provided is given in good faith and believed to be current and correct at the time of publication. Ambic Equipment Ltd cannot accept responsibility for errors or omissions contained in this document.